

Section 17
TABLE OF CONTENTS
Conveyors

Section:	Page
17.A General	17-1
17.B Operation	17-5
17.C <u>Training</u>	17-6

THIS PAGE INTENTIONALLY LEFT BLANK

SECTION 17

Conveyors

17.A General. Conveyor systems shall be constructed and installed in accordance with the manufacturer's recommendations.

17.A.01 Inspection, maintenance, and repair. These activities shall be performed in accordance with the manufacturer's recommendations by a Qualified Person (QP). The entire system shall be visually inspected daily before start up.

a. No maintenance shall be performed when a conveyor is in operation except for the following:

(1) If lubrication is to be done while the conveyor is in motion, lubrication points shall be accessible through guard openings which are small enough that fingers cannot reach the hazardous locations. Only trained personnel who are aware of the hazards of the conveyor in motion shall be allowed to lubricate a conveyor that is operating; and

(2) When adjustments or maintenance is required while the conveyor is in operation, only trained personnel who are aware of the hazards shall be permitted to make the adjustment or maintenance. If guards need to be removed for the adjustment or maintenance, the conveyor MUST be locked out prior to removing the guards.

b. Hazardous Energy Control Procedures shall be used for maintenance and servicing other than lubrication which is done without removing guards. > See Section 12.

c. Safe access shall be provided to permit inspection, lubrication, repair and maintenance activities.

17.A.02 Safety devices.

a. On all conveyors where reversing or runaway are potential hazards or the effects of gravity create a potential for hazardous uncontrolled lowering, anti-runaway devices, brakes, backstops, or other safeguards shall be installed to protect persons from injury and property from damage.

b. Conveyor systems shall be equipped with a time-delay audible and visual warning signal to be sounded immediately before starting of the conveyor. On overland conveyor systems, the devices shall be required only at the transfer, loading, and discharge points and those points where personnel are normally stationed.

c. Safety devices shall be arranged to operate in such a manner that if power failure or a failure of the device occurs a hazardous condition would not result. The safety devices shall be designed to prevent the conveyor from restarting until the safety device is manually reset.

17.A.03 All exposed moving machinery parts that present a hazard shall be mechanically or electrically guarded or guarded by location.

a. Nip and shear points shall be guarded.

b. Take-up mechanisms may be guarded as an entity by placing standard railings or fencing, and warning signs, around the area in lieu of guarding each nip and shear point.

c. In the case of a trolley conveyor when mechanical or electrical guarding would render the conveyor unusable, prominent and legible warnings shall be posted in the area or on the equipment and, where feasible, areas barricaded or lines marked on the ground to indicate the hazard area.

d. Guards shall be provided at points where personnel could contact cables, chains, belts, and runaways of exposed bucket conveyors.

e. Unless guarded by location, those sections of chain conveyors that cannot be enclosed without impairing the function shall be provided with warning signs or personnel barriers.

f. Trolley conveyors shall be provided with spill guards, pan guards, or the equivalent if there is a potential for material to fall off the conveyor and endanger personnel or equipment.

g. At transfer, loading, and discharge points, unconfined and uncontrolled free fall of material that may result from flooding, ricocheting, overloading, trajectory, leakage, or a combination thereof, shall be prevented if the material would create a hazard to personnel.

➤ Note: In the absence of a guard specifically erected to protect personnel, warnings shall be provided to restrict unauthorized personnel from entering such hazardous areas.

h. At all points along the conveyor, except at points where loads are removed from or placed on a conveyor or where a conveyor discharges to or receives material from another conveyor, provisions shall be made to eliminate the possibility of loads or material being dislodged from the conveyor.

i. The build-up of excess material shall be removed from all points along the conveyor.

17.A.04 Access.

a. Crossovers or underpasses with safeguards shall be provided for passage over or under all conveyors: crossing over or under conveyors is prohibited except where safe passageways are provided.

b. Whenever conveyors pass adjacent to, or over, work areas, roadways, highways, railroads, or other public passageways, protective guards shall be installed. The guards shall be designed to catch and hold any load or material that may fall off or become dislodged from the system.

c. Where conveyors are operated in tunnels, pits, and similar enclosures, ample room shall be provided to allow safe access and operating space for all personnel.

17.A.05 Operating controls.

a. Unless the design, construction, and operation of a conveyor is clearly non-hazardous to personnel, emergency stop buttons, pull cords, limit switches, or similar emergency devices shall be provided at the following locations:

(1) Operator stations;

(2) Loading arms;

(3) Transfer points; and

(4) Other potentially hazardous locations on the conveyor path not guarded by location or guards.

b. Emergency stop buttons shall be red in color, easily identifiable and readily accessible. They shall not be protected with collars or other devices which might make it difficult to activate.

c. Emergency stop devices shall act directly on the control of the conveyor concerned and shall not depend on the stopping of any other equipment. If a multi-conveyor system, the emergency stop shall stop all conveyors that are tied together.

d. Emergency stop devices shall be installed so that they cannot be overridden from other locations.

e. Starting controls shall be GREEN in color and protected from accidental activation.

f. All controls shall be clearly labeled to identify their function.

g. Conveyor controls shall be arranged so that in case of an emergency stop, manual reset or restart is required at the location where the emergency stop was initiated to resume conveyor operations.

17.A.06 Control stations shall be arranged and located so that the operation of the equipment is visible from them.

17.A.07 Gates and switches.

a. Power-positioned gate and switch sections shall be provided with devices that will prevent these sections from falling in case of power failure.

b. Means shall be provided on all gates and switch sections to prevent conveyed material from discharging into the open area created by lifting of the gate or switch.

17.A.08 Counterweights.

a. When counterweights are supported by belts, cables, chains, or similar means, the weights shall be confined in an enclosure to prevent the presence of personnel beneath the counter-weight, or the arrangement shall provide a means to restrain the falling weight in case of failure of the normal counterweight support.

b. When counterweights are attached to lever arms they shall be securely fastened.

17.A.09 When two or more conveying systems are interfaced, special attention shall be given to the interfaced area to ensure the presence of adequate guarding and safety devices.

17.A.10 Hoppers and chutes.

a. All openings to the hopper and chutes shall be guarded to prevent persons from accidentally stepping into them. If guards are not practical, warning signs shall be posted.

b. Dump hoppers having the hopper flush with the floor and which by their use cannot be guarded shall be equipped with grating having a maximum opening of 4 in (10 cm) and heavy enough to withstand any load which may be imposed on it. If the openings in the grating are larger or if no grating is provided, temporary railing shall be placed around ground level hoppers when dumping operation are not in progress. During dumping operation, warning signs shall be placed in conspicuous locations warning personnel of an open pit.

17.A.11 Mobile conveyors.

- a. Mobile conveyors shall be provided with brakes or other position locking devices for each degree of motion where movement would present a hazard.
- b. Mobile conveyors shall be designed to be stationary against runaway and stable against overturning under normal conditions of operation.
- c. When an operator is required on a mobile conveyor, a platform or cab shall be provided for his/her protection.

17.A.12 Portable conveyors.

- a. The raising and lowering mechanism for the boom of a portable conveyor shall be provided with a safety device that will hold the boom at any rated angle of inclination.
- b. Portable conveyors shall be stable so that the conveyor will not topple when used with the manufacturer's rating and in a manner in which it was intended or when being moved.

17.A.13 Screw Conveyors.

- a. Screw conveyors shall not be operated unless the conveyor housing completely encloses the conveyor moving elements and power transmission guards are in place, except that if the conveyor must have an open housing as a condition of use, the entire conveyor shall then be guarded by railing, fence, or by location.
- b. Feed openings for shovel, front-end loader, or other manual or mechanical equipment shall be constructed in such a way that the conveyor screw is covered by grating. If the nature of the material is such that grating cannot be used, then the exposed section of the conveyor shall be guarded by a railing and warning signs shall be posted.

17.A.14 Conveyors shall be properly grounded before use and all connections, switches and cables shall conform to the National Electric Code (NEC).

17.B Operation.

17.B.01 Conveyor equipment shall be used to convey only those materials for which it was designed and within the rated capacities and speeds.

17.B.02 Flight and apron conveyors shall be "jogged" or hand run through at least one complete revolution at installation to check design clearances prior to running under automatic power.

17.B.03 A conveyor that could cause injury when started shall not be started until all personnel in the area are alerted by a signal or by a designated person that the conveyor is about to start.

17.B.04 When a conveyor that could cause injury when started is automatically controlled or must be controlled from a remote location, an audible warning device shall be provided. The device shall be clearly audible at all points along the conveyor where personnel may be present.

a. The warning device shall be activated by the controller device that starts the conveyor and shall continue for a period of time before the conveyor starts. A flashing light or similar visual warning shall be used with the audible device.

b. If a conveyor system is not exposed to the public, and if function of the system would be seriously hindered or adversely affected by the required time delay or where the intent of the warning may be misinterpreted, clear, concise, and legible warning signs shall be provided and indicate that the system may be started at any time, that danger exists, and that personnel must keep clear. These warnings signs shall be provided along the conveyor at areas that are not guarded or protected by their location.

17.B.05 Before restarting a conveyor that has been stopped because of an emergency, an inspection of the conveyor shall be conducted and the cause of the emergency stop determined.

17.B.06 The area around loading and unloading points shall be kept clear of obstructions that could create a hazard.

17.B.07 Applying a belt dressing or other foreign material to a rotating drive pulley or conveyor belt shall be avoided.

17.B.08 Flight and apron conveyors handling sticky materials that tend to build up shall be cleaned as often as required for safe operation.

17.C Training.

17.C.01 Only trained personnel shall be permitted to operate a conveyor. Training shall include instruction in operation under normal conditions and in emergencies.

17.C.02 Riding on conveyors is prohibited.

17.C.03 Personnel working with or near a conveyor shall be:

a. Instructed as to the location and operation of pertinent stopping devices; and

- b. Prohibited from wearing loose or baggy clothing, jewelry or long hair.

17.C.04 Only trained personnel shall track a conveyor belt that must be done while the conveyor is operating.

STUDY QUESTIONS

1. Conveyor systems shall be equipped with a time-delay _____ warning signal to be sounded immediately before starting of the conveyor.
 - a. audible and visual
 - b. sequenced
 - c. repetitive
 - d. visual and tactile

2. A conveyor that could cause injury when started shall not be started until all personnel in the area are alerted by a _____ that the conveyor is about to start.
 - a. signal or by a designated person
 - b. sequenced warning light
 - c. repetitive bursts of sound
 - d. visual warning sign

3. What action must be taken before restarting a conveyor that has been stopped because of an emergency?
 - a. perform an inspection of the conveyor
 - b. attempt an immediate restart
 - c. determine who is at fault in the incident
 - d. review the conveyor safety program

4. Emergency stop buttons must meet each of the following criteria, EXCEPT:
 - a. red in color
 - b. easily identifiable
 - c. readily accessible
 - d. protected with collars

5. Personnel working with or near a conveyor should wear loose clothing to prevent being snagged by moving parts.
 - a. True
 - b. False